



Jan 7 1889

I commenced Survey of Section

22 Town 7 North,

Range 5 West.

W. W. Cogoton
County Surveyor.

COURSE.	DISTANCE.	REMARKS.
North	25.15	From S E
	40.15	to A N corner of Bloomfield
	40.15	to E 1/4 From S 1/4 20 55
North	40.07	to A E
		From A E
West	39.19	to A 1/4 From A 1/4 20 4
West	39.33	to A N 30 55
		From A N
South	40.25	to N 1/4 20 19
	80.50	to S N
		From S N
East	39.76	to S 1/4
	79.52	to S E

Corners Established.	Monument.	Bearing Trees.	Diameter in Inches.	Course.	Links Distant.	
Re 1st A N		B Walnut 16	3 59 N	22		
		Ash 12	3 64 E	20		
E 1/4	Stone	W Oak 18	A 82 E	54		
Re 2nd E 1/4	Stone	Beech 24 cressy locust 24	3 86 1/2 E 3 86 1/2 E	179 1/2		
Re 3rd A 1/4	Stone	B Walnut 24	3 86 1/2 E	223		
A 4 A E		Gum 16	3 25 1/2 N	47 48		
		Both Gov trees standing but east one dead				
		B Gum 48	A 79 N	28		
		W Oak 12	A 69 E	36		
3 1/4 A E	Stone	B Oak 15	A 26 N	14		
		W Oak 20	A 78 N	43		
W 1/4 A E		B Oak 12	3 54 N	9		
		B Walnut 12	3 54 N	13		
E 1/4 A E	Stone	B Oak 15	A 2 E	6 1/2	448	
Cent A E	Stone	W Walnut 12	W 78 E	7	448	
		" "	3 69 E	6		
8.21 W of E 1/4	Stone	Sycamore 20	3 70 E	43		
		W Oak 8	3 22 1/2 E	21		
8.21 E of 3 1/4 A E	Stone					
		S 1/4	Elm 15	3 67 N	69	
		W 1/4 3 E	B Walnut 6	A 12 1/2 E	28	
			Stone below plow depth west 2 1/2			
W 1/4 S N	Stone	Hickory 24	A 81 1/2 E	45		
		W 1/4	Stone	North	86	
		On south line of sec				
		at west side of John St stone				
		805 ft N of E 1/4				
		5 8 1/4	Stone			